

AMENDMENTS TO THE CLAIMS

Please amend claims 1, 7, 10 and 13 as follows:

1. (currently amended) A method of mixing a cosmetic preparation at a point of sale, the method comprising:

- a) providing a container comprising an open top;
- b) adding a first base suspension that is free of colorant;
- c) adding one or more suspensions comprising one or more colorants on top of the first base suspension;
- d) adding a second base suspension on top of the one or more suspensions comprising one or more colorants, the second base suspension also being free of colorant;
- e) closing the open top of the container with a lid; and
- f) mixing the suspensions within the container by applying mechanical energy to the closed container.

2. (original) The method of claim 1 wherein the container comprises a neck portion that terminates at the open top, and the closing of the open top of the container with a lid further comprises inserting a plug down into the neck of the container to prevent the suspensions from splashing upward into the neck during the mixing of the suspensions.

3. (original) The method of claim 1 wherein the first base suspension comprises talc and the second base suspension comprises titanium dioxide and silicone either combined or in separate suspensions.

4. (original) The method of claim 1 wherein the one or more suspensions comprising one or more colorants comprises a first suspension comprising a red colorant, a second suspension comprising a yellow colorant and a third suspension comprising a black colorant.

5. (original) The method of claim 1 wherein the mixing by applying mechanical energy comprises the use of a gyroscopic mixer that rotates the closed container about two different but intersecting axes.

6. (original) The method of claim 1 wherein the mixing by applying mechanical energy comprises the use of a rotary mixer that rotates the closed container about two different but intersecting axes.

7. (currently amended) A method of mixing a cosmetic preparation at a point of sale, the method comprising:

- a) providing a container comprising a neck that terminates at an open top;
- b) adding a first base suspension to the container that is free of colorant;
- c) adding a second suspension comprising one or more colorants on of the first suspension;
- d) adding a third suspension comprising one or more colorants on top of the second suspension;
- e) adding a fourth suspension comprising one or more colorants on top of the third suspension;
- f) adding a fifth base suspension on top of the fourth suspension, the fifth base suspension being free of colorant;
- e) inserting a plug into the neck of the container to close the open top of the container; and
- f) mixing the suspensions within the container by applying mechanical energy to the closed container.

8. (original) The method of claim 7 wherein the mixing by applying mechanical energy comprises the use of a gyroscopic mixer that rotates the closed container about two different but intersecting axes..

9. (original) The method of claim 7 wherein the mixing by applying mechanical energy comprises the use of a rotary mixer that rotates the closed container about two different but intersecting axes.

10. (currently amended) A method of mixing a cosmetic preparation at a point of sale, the method comprising:

- a) providing a container comprising a neck terminating in an open top and a bottom;
- b) adding a suspension comprising talc to the container and coating the sidewall and bottom with the suspension comprising talc, the suspension comprising talc being free of colorant;
- c) adding one or more suspensions comprising one or more colorants including black, red and yellow colorants on top of the suspension comprising talc;
- d) adding one or more suspensions comprising titanium oxide and silicone on top of the one or more suspensions comprising one or more colorants, the suspension comprising titanium dioxide being free of colorant;
- e) closing the open top of the container by inserting a plug into the neck of the container; and
- f) mixing the suspensions within the container by applying mechanical energy to the closed container.

11. (original) The method of claim 10 wherein the mixing by applying mechanical energy comprises the use of a gyroscopic mixer that rotates the closed container about two different but intersecting axes.

12. (original) The method of claim 10 wherein the mixing by applying mechanical energy comprises the use of a rotary mixer that rotates the closed container about two different but intersecting axes.

13. (currently amended) A method of mixing a cosmetic preparation at a point of sale, the method comprising:

- a) providing a container comprising an open top;
- b) adding a suspension comprising one or more of talc, titanium oxide and silicone to the container, said suspension being free of colorant;
- c) adding one or more suspensions comprising one or more colorants on top of the suspension comprising one or more of talc, titanium oxide and silicone;

d) adding another suspension comprising one or more of titanium oxide, silicone and talc on top of the one or more suspensions comprising one or more colorants, said another suspension being free of colorant;

e) closing the open top of the container with a lid; and

f) mixing the suspensions within the container by applying mechanical energy to the closed container.

14. (original) The method of claim 13 wherein part (b) further comprises coating the bottom of the container with the suspension comprising one or more of talc, titanium oxide and silicone to prevent the one or more suspensions comprising one or more colorants from coating the sidewall of the container.

15. (original) The method of claim 13 wherein the one or more suspensions comprising one or more colorants comprises a first suspension comprising a red colorant, a second suspension comprising a yellow colorant and a third suspension comprising a black colorant.

16. (original) The method of claim 13 wherein the mixing by applying mechanical energy comprises the use of a gyroscopic mixer that rotates the closed container about two different but intersecting axes.

17. (original) The method of claim 13 wherein the mixing by applying mechanical energy comprises the use of a rotary mixer that rotates the closed container about two different but intersecting axes.